



DATSCO RESOURCES INC

2275 UPPER MIDDLE ROAD EAST
SUITE 101 OAKVILLE
ON L6H0C3 CA
PHONE: +14373402451

TECHNICAL DATA SHEET

Material: Hydroxy Propyl Methyl Cellulose (HPMC)

Cas No.: 9004-65-3

Product of Origin: P.R. China

DESCRIPTION OF THE PRODUCT

HPMC is kind of white or yellowish powder or grains. HPMC is nearly insoluble in anhydrous ethanol ethyl ether and acetone. It is swelled in cold water to form a transparent or slight cloudy solution. It can be dissolved into some organic solvents and in water-organic solvent mixed

SALES SPECIFICATION

GRADE	RS50	RS100	RS150	RS200
Appearance	White or slightly yellow granular powder			
Methoxy (WT%)	19.0-24.0	19.0-24.0	19.0-24.0	19.0-24.0
Hydroxypropoxy (WT%)	4.0-12.0	4.0-12.0	4.0-12.0	4.0-12.0
Loss on Drying (WT%) Max.	5.0	5.0	5.0	5.0
PH Value (25°C)	5.0-8.0	5.0-8.0	5.0-8.0	5.0-8.0
Viscosity mPa.s (2% Solution)	35000-55000	80000-120000	120000-180000	180000-250000



DATSCO RESOURCES INC

2275 UPPER MIDDLE ROAD EAST
SUITE 101 OAKVILLE
ON L6H0C3 CA
PHONE: +14373402451

APPLICATION SCOPE (SUGGESTION)

GRADE	RECOMMEND APPLICATION
DAS50	Plaster Putty Plster Maortar Tile Bonding Agent EIFS Adhesives
DAS100	Plaster Putty Plaster Mortar EIFS Adhesives
DAS150	Plaster Putty Plaster Martar EIFS Adhesives
DAS200	Plaster Putty EIFS Adhesives

PACKAGE

Compound triple paper-plastic square bottom value package. N.W. is 25kg/per bag. Or as per customers' requirement

STORAGE

Store it in a cool, dry place temperature below 35°C, max. Stacking layers should not be over 10 layers

SHELF LIFE

12 month in the proper condition. And after valid period, if the products have not lumped, it could still be used.