



DATSCO RESOURCES INC

2275 UPPER MIDDLE ROAD EAST
SUITE 101 OAKVILLE
ON L6H0C3 CA
PHONE: +14373402451

TECHNICAL DATA SHEET

Material: Re-dispersible Emulsion Powder
Product of Origin: P.R. China

DESCRIPTION OF THE PRODUCT

Re-dispersible emulsion powder is type of co-polymerized mainly used as the additives for dry mortar or cement based products in construction industry.

SALES SPECIFICATION

GRADE	DAS-04	DAS-05
COMPOSITION	Vinyl Acetate/VeoVa	Vinyl Acetate/Veovo/Ethylene
APPEARANCE	White powder, freely flow	White powder, freely flow
SOLID CONTENTS(%)	≥98.0	98.0
ASH CONTENT	10±2%	10±2%
STACKING DENSITY (G/L)	400-600	400-600
AVERAGE PARTICLE DIAMETER (μ M)	70-100	70-100
VISCIDITY OF 50% WATER SOLUTION (PA S)	0.5-2.0	0.5-2.0
PH VALUE	6-8	6-8
LOWEST MEMBRANE-FORMING TEMPERATURE	Approx. 5 °C	Approx. -1 °C
TG TEMPRETURE	Approx. 18 °C	Approx. 6 °C



DATSCO RESOURCES INC

2275 UPPER MIDDLE ROAD EAST
SUITE 101 OAKVILLE
ON L6H0C3 CA
PHONE: +14373402451

APPLICATION SCOPE (SUGGESTION)

DAS-04	<ol style="list-style-type: none">1. Used as additives for tile adhesives to increase adhesive bonding strength2. Used as dry mortar additives to improve bonding strength3. Used as gravity flow mortar and self-leveling ground material
DAS-05	<ol style="list-style-type: none">1. Used as additives for surface mortar of exterior building to improve flexibility2. Used as soft putty for exterior walls of buildings3. Used in flexibility-demanding cement-based polymer mortar products

PACKAGE

Compound triple paper-plastic square bottom value package. N.W. is 25kg/per bag. Or as per customers' requirement

STORAGE

Store it in a cool, dry place temperature below 35°C, max. Stacking layers should not be over 10 layers

SHELF LIFE

12 month in the proper condition. And after valid period, if the products have not lumped, it could still be used.